

## DAFTAR PUSTAKA

- [1] R. Abudi, Y. Mokodompis och A. N. Magulili, "Stigma Terhadap Orang Positif COVID-19," *Jambura Journal of Health Sciences and Research*, vol. 2, nr 2, pp. 77-84, 2020.
- [2] I. N. Sandi, "Pengaruh Suhu Dan Kelembaban Relatif Udara Terhadap Penampilan Fisik Dalam Olahraga," *Seminar Nasional Prodi Biologi F. MIPA UNHI*, pp. 282-287, 2014.
- [3] B. J. Huang, C. J. Chin och C. L. Duang, "A design method of thermoelectric cooler," *International Journal of Refrigeration*, 2000.
- [4] S. P. Nalavade, A. D. Patange, C. L. Prabhune, S. S. Mulik och M. S. Shewale, "Development of 12 channel temperature acquisition system for heat exchanger using MAX6675 and Arduino interface," in Chandrasekhar U., Yang LJ., Gowthaman S. (eds) *Innovative Design, Analysis and Development Practices in Aerospace and Automotive Engineering, Lecture Notes in Mechanical Engineering*, 2019, pp. 119-125.
- [5] L. Louis, "Working Principle of a Arduino and Using It," *International Journal of Control, Automation, Communication and Systems (IJCACS)*, vol. 1, nr 2, 2016.
- [6] Arduino, "Arduino Nano," 2019. [Online]. Available: <https://www.arduino.cc/>. [Använd 3 08 2020].
- [7] F. Khoucha, S. Mouna Lagoun, K. Marouani, A. Kheloui, M. Benbouzid, M. El Hachemi Benbouzid och S. Member, "Hybrid Cascaded H-Bridge Multilevel-Inverter Induction-Motor-Drive Direct Torque Control for Automotive Applications Hybrid Cascaded H-Bridge Multilevel-Inverter Induction-Motor-Drive Direct Torque Control for Automotive Applications Hybrid Cascaded H-Br," *IEEE Transactions on Industrial Electronics, Institute of Electrical and Electronics Engineers*, vol. 57, nr 3, 2010.
- [8] M. Todica, "Reading X, Y Coordinates with Optical Mouse and Sending Data Via Internet with NodeMcu-ESP8266," *Studia Universitatis Babeş-Bolyai Physica*, vol. 63, nr 1-2, pp. 27-35, 2018.